

2014/11/10

FORMOZA FD1

SER	SIZE	PR	LI/SS	OVERALL mm	Diameter in	Section Width mm	Section Width in	Standard Rim in	Approved Rim Width	Tread Width mm	Tread Width in	Tread Depth in	Tread Depth mm	Weight KG	MAX. PSI cold	Max. Load KGS	Max. Load LBS	UTQG	Side Wall	P-Code
45	165/45R15		68V	531	20.9	168	6.6	5.5	5.0- 6.0	154	6.1	10	7.9	6.5	44	315	695	320A A	BSW	176K5AFE
50	165/50R15		73V	548	21.6	169	6.7	5.0	4.5- 6.0	148	5.8	10	8.0	7.0	44	365	804	360A A	BSW	176J5AFE
50	205/50R16		87V	611	24.0	213	8.4	6.5	5.5- 7.5	187	7.4	10	8.1	9.4	44	545	1202	360A A	BSW	170J6AFE
55	155/55R14		69V	526	20.7	165	6.5	5.0	4.5- 5.5	144	5.7	10	7.6	6.3	44	325	717	360A A	BSW	17514AFE
	165/55R14		72V	538	21.2	170	6.7	5.0	4.5- 6.0	148	5.8	10	7.7	6.7	44	355	783	360A A	BSW	17614AFE
55	195/55R15		85V	600	23.6	197	7.7	6.0	5.5- 7.0	181	7.1	10	8.1	8.7	44	515	1136	360A A	BSW	17915AFE
55	205/55R16		91V	632	24.9	224	8.8	6.5	5.5- 7.5	184	7.2	10	8.3	9.4	44	615	1356	360A A	BSW	17016AFE
	215/55R16		93V	641	25.3	224	8.8	7.0	6.0- 7.5	194	7.6	10	8.3	10.7	44	650	1433	360A A	BSW	17A16AFE
60	205/60R13		87H	576	22.7	202	7.9	6.0	5.5- 7.5	164	6.5	10	8.1	8.5	44	545	1202	460A A	BSW	170H3AFE
60	165/60R14		75H	555	21.9	163	6.4	5.0	4.5- 6.0	132	5.2	10	7.8	6.5	44	387	854	460A A	BSW	176H4AFE
	175/60R14		79H	567	22.3	176	6.9	5.0	5.0- 6.0	136	5.4	10	7.9	6.6	44	437	964	460A A	BSW	177H4AFE
	185/60R14		82H	578	22.8	186	7.3	5.5	5.0- 6.5	148	5.8	10	7.9	7.4	44	475	1047	460A A	BSW	178H4AFE
60	195/60R15		88H	614	24.2	198	7.8	6.0	5.5- 7.0	158	6.2	10	8.1	8.2	44	560	1235	460A A	BSW	179H5AFE
65	185/65R14		86H	596	23.5	190	7.5	5.5	5.0- 6.5	144	5.7	10	8.0	7.5	44	530	1168	460A A	BSW	178G4AFE
65	195/65R15		91H	636	25.0	198	7.8	6.0	5.5- 7.0	152	6.0	10	8.2	8.5	44	615	1356	460A A	BSW	179G5AFE
	205/65R15		95H	647	25.5	205	8.1	6.0	5.5- 7.5	160	6.3	10	8.3	10.1	44	690	1521	460A A	BSW	170G5AFE